

Precision Progressive

SWISSCOAT Technical Specification Plastic

Precision						
Index	1.5	1.53	1.59	1.61	1.67	1.74
Material	Clear SunAdapt XTRActive Transitions Gen8 Nupolar Drivewear	Clear NXT XTRActive Transitions Gen8	Clear Transitions Gen8 Drivewear	Clear Armour UV++ Armour Sun UV++ SunAdapt XTRActive Transitions Gen8 Nupolar	Clear Armour UV++ Armour Sun UV++ SunAdapt XTRActive Transitions Gen8 Nupolar	Clear Armour UV++ Armour Sun UV++ Transitions Gen8
Max Diameter	75+5	75+5	75+5	75+5	75+5	75+5
Fitting Height	15mm to 19mm	15mm to 19mm	15mm to 19mm	15mm to 19mm	15mm to 19mm	15mm to 19mm
Rx Power Range	+6.00 ~ -8.00	+6.00 ~ -8.00	+6.00 ~ -9.00	+8.00 ~ -10.00	+8.00 ~ -11.00	+7.00 ~ -12.00
Addition Power	A+0.75 ~ A+3.50	A+0.75 ~ A+3.50	A+0.75 ~ A+3.50	A+0.75 ~ A+3.50	A+0.75 ~ A+3.50	A+0.75 ~ A+3.50
Power Compensation	YES	YES	YES	YES	YES	YES

Any power exceeds the power range, contact SWISSCOAT customer service officer.